

CITYBEAM LED SL84

• **SOURCE**

n.84 Hi-Power LED
(22 red, 22 green, 22 blue, 18 white)
220W total light power

Lumen:
Red 3400lm, Green 6000lm, Blue 33W, White 7200lm

• **OPTIC**

4° ultranarrow (35 mm lenses)

• **TILT**

Manual 160°

• **CONTROL**

Standard interface: RS-485, optocoupled input
Protocol: USITT DMX512

• **CONNECTIONS**

Signal: 4pin IP 67 connector (male-female)
Main Power: 3x1mm cable 1,5mt.
Available as accessories:
- Wireless DMX receiver

• **SAFETY**

n. 2 eyebolts for safety chains

• **SETUP AND CONFIGURATION**

RDM ready
Control panel with touch technology
Led display with flip function
Dedicated DMX channel for white balance
DMX or Auto mode with Master-Slave function
Intelligent temperature control
Flicker-free function
Smooth dimming function
Halogen simulation
CYM simulation

• **RATING PROTECTION**

IP 67

• **DMX CHANNELS**

- 9CH mode
- 5CH mode
- 4CH mode

• **POWER SUPPLY**

Switching power supply
Rated voltage 100-240V~
Frequency 47-65Hz
Rated current 1,1A@230V - Fuse T5A
Active PFC 0,95
Power consumption 250W

• **PHYSICAL**

WxDxH: 615x185x420 mm
Weight: 18,5 Kg.

CITYBEAM LED SL42

• **SOURCE**

n.42 Hi-Power LED
(11 red, 11 green, 11 blue, 9 white)
110W total light power

Lumen:
Red 1700lm, Green 3000lm, Blue 16,5W, White 3600lm

• **OPTIC**

4° ultranarrow (35 mm lenses)

• **TILT**

Manual 160°

• **CONTROL**

Standard interface: RS-485, optocoupled input
Protocol: USITT DMX512

• **CONNECTIONS**

Signal: 4pin IP 67 connector (male-female)
Main Power: 3x1mm cable 1,5mt.
Available as accessories:
- Wireless DMX receiver

• **SAFETY**

n. 2 eyebolts for safety chains

• **SETUP AND CONFIGURATION**

RDM ready
Control panel with touch technology
Led display with flip function
Dedicated DMX channel for white balance
DMX or Auto mode with Master-Slave function
Intelligent temperature control
Flicker-free function
Smooth dimming function
Halogen simulation
CYM simulation

• **RATING PROTECTION**

IP 67

• **DMX CHANNELS**

- 9CH mode
- 5CH mode
- 4CH mode

• **POWER SUPPLY**

Switching power supply
Rated voltage 100-240V~
Frequency 47-65Hz
Rated current 0,55A@230V - Fuse T5A
Active PFC 0,95
Power consumption 125W

• **PHYSICAL**

WxDxH: 353x185x420 mm
Weight: 12 Kg.