


SMART 17 TECHNICAL FEATURES / CARATTERISTICHE TECNICHE SMART 17



ITEM	RGBWA [KEY features] SMART 17
LEDs	13 RGB-NW (White 4000K) + 4 PC-Amber (NICHIA hi-power LEDs)
Total light power	33W
Lumen	R 520, G 850, B 300, W 800, A 500
Optics	24° (23mm lenses) PMMA 8N On request: 12°, 36°, 10°x30°, 15°x55°
Tilt	175° manual
Connections	Main IN: 1.5mt 3x1 cable with bare ends DMX: IN-OUT 3pins IP67 connectors
Control	Standard interface: RS-485 Protocol: USITT DMX512 / RDM > Available as accessories: Wireless DMX receiver
Setup and Configuration	RDM control/configuration or by DRS (remote control device) Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Intelligent temperature control Halogen simulation CYM simulation Flicker-free function Smooth dimming function
Power supply	Universal 100/240VAC, 47-63Hz Active PFC: >0.9@230V
Current	0,16A@230Vac
Power	36W
DMX channels	10CH mode, 7CH mode, 6CH mode, 5CH mode
Physical	175x95x215 mm
Weight	2,2 Kg
Material	Housing in die-cast aluminium - bracket in stainless steel - ultra clear white 4mm tempered glass



ITEM	FIXTURE	[KEY features]
LEDs	Monochromatic White Balance	17 NICHIA-NVSL219C 4000K available 2700K, 5000K, 6500K On request: red, green, blue or amber 9 warm white (2700K) + 8 cool white (6500K) NICHIA-NVSL219C
Total light power		28W
Lumen	Monochromatic White Balance	3000lm @4000K 2500lm @4000K
Optics		24° (23mm lenses) PMMA 8N - On request: 12°, 36°, 10°x30°, 15°x55°
Tilt		270° manual
Connections		IN-OUT DMX 3pins IP67 connectors (none for Plug-in version) - 1.5mt 3x1 cable. with bare ends
Control - Setup		DMX 512 / RDM - RDM / DRS Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Halogen simulation Flicker-free function Smooth dimming function
Power consumption		32W - 0,12A@230V
Voltage range		Universal 100/240VAC, 47-63Hz, Active PFC: >0.9@230V
DMX channels		Monochromatic : 3CH mode, 1CH mode (none for Plug-in version) White Balance: 4CH mode, 2CH mode, 1CH mode
Physical		175x95x215 mm
Weight		2,2 Kg
Material		Housing in die-cast aluminium - bracket in stainless steel - ultra clear white 4mm tempered glass