

TECHNICAL FEATURES / CARATTERISTICHE TECNICHE



• SOURCE

n. 12 (5050-20W-RTBH) LEDs
Total out lumen: R 750, G 1800, B 300, W 1700
Total light power: 40W

• OPTIC (38 mm lenses)

8°, 15°, 25°, 40°, 60° or 10°x30° beam

• TILT

manual 0°, 3°, 6°

• CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512 / RDM

• CONNECTIONS

Signal: 3pin cable 70cm. (could be wired with 4PIN connector)

Available as accessories:

- Wireless DMX receiver

Main Power: 3pin cable 70cm. with bare ends

• SETUP AND CONFIGURATION

RDM Control/configuration or individually by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

• IP67 RATING PROTECTION

• IK10 RATING

• POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF > 0.97@230VAC

Current: 0.2A@230VAC

Power: 45W

Fuse T3,15A (inside fixture)

• DMX CHANNELS

9CH mode, 6CH mode, 5CH mode, 4CH mode

• PHYSICAL

WxDxH: 1063x182x133 mm

Weight: 15 Kg.



• SOURCE

n. 24 warm, neutral, cool LEDs monochromatic

n. 12 (2700K) + 12 (6500K) white balance

On request: red, green, blue or amber

Total out lumen: 48W (monochromatic) - 40W (white balance)

Total out power: 7500 (monochromatic) - 6000 (white balance)

• OPTIC (38 mm lenses)

Monochromatic: 4°, 8°, 15°, 40°, 60°, 10°x30° beam

White balance: 8°, 15°, 40°, 60° beam

• TILT

manual 0°, 3°, 6°

• CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512 / RDM

• CONNECTIONS

Signal: 3pin cable 70cm. (could be wired with 4PIN connector)

Available as accessories:

- Wireless DMX receiver

Main Power: cable 70cm. with bare ends

• SETUP AND CONFIGURATION

RDM Control/configuration or

individually by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

Flicker-free function

Smooth dimming function

• IP67 RATING PROTECTION

• IK10 RATING

• POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF > 0.97/230VAC

Current: 0.18A@230VAC

Power: 40W (monochromatic) - 40W (white balance)

Fuse T3,15A (inside fixture)

• DMX CHANNELS

4CH mode, 2CH mode, 1CH mode (white balance)

3CH mode, 1CH mode (monochromatic)

• PHYSICAL

WxDxH: 1063x182x133 mm

Weight: 15 Kg.

For PLUG IN version

- Main Power: cable 70cm.

- NO CONTROL

- NO SETUP and CONFIGURATION

- NO DMX CHANNELS