



LEDX.NO

LED expert AS
Torpumveien 543
1788 Halden

E-post: post@ledx.no
Tlf: 909 54 606

400W IP65 outdoor gobo projector

Specification

- ◆ Input Voltage: AC100-240V, 50-60Hz
- ◆ Rated Power: 420W
- ◆ Light Source: 400W LED integrated with ORSRAM chip
- ◆ Color Temperature: 8000K
- ◆ Luminous flux: >24000lm
- ◆ Color rendering index: 90
- ◆ Projection angle: 15°/20°/30°/45°/15° selectable
- ◆ Projection distance: 8-250m
- ◆ Waterproof rating: IP65
- ◆ Control mode: Auto-propelled/Master-slave/DMX512
- ◆ Suitable locations: Squares, parks, scenic spots, etc.
- ◆ Operating environment: -30°C to 45°C
- ◆ Cooling system: Copper pipe radiator + fan cooling
- ◆ Net weight: 12KG
- ◆ Dimensions: 375*320*380mm



Effects

- ◆ Strobe: 1-20Hz fast strobe, with pulse strobe and synchronous/asynchronous strobe functions
- ◆ Dimming: Smooth dimming without flicker
- ◆ Effects panel: 1 dynamic shadow panel
- ◆ Pattern panel: 6 patterns, independently rotatable, bidirectional flowing water effect



Software and Control

- ◆ Control Channels: Standard 12 channels
- ◆ Transmission Protocol: DMX512
- ◆ Menu Display: LCD screen, Chinese and English languages can be switched freely, font can be rotated 180°, with automatic over-temperature protection.

Product features

- ◆ Full range of lens angles from 15° to 60°, interchangeable at will.
- ◆ Employs an 8-element ultra-high-definition lens for sharp image contours.
- ◆ All-aluminum alloy casing for high structural strength and black anodized finish.
- ◆ Uses a copper pipe finned heat sink for heat dissipation.
- ◆ Lamp housing is made of high-strength die-cast aluminum, UV resistant, high-temperature resistant, and anti-aging.

